



SIMATIC DP,BUS CONNECTOR FOR PROFIBUS UP TO 12 MBIT/S 35 DEGREE ANGLE CABLE OUTLET, IPCD TECHNOLOGY FAST CONNECT, WITHOUT PG SOCKET 15,8 X 54 X 39,5 MM (WXHXD),

Transfer rate

- with PROFIBUS

9.6 kbit/s ... 12 Mbit/s

**Interfaces**

Number of electrical connections

- for PROFIBUS cables
- for network components and terminal equipment

2

1

Design of the electrical connection

- for network components and terminal equipment

9-pin Sub-D plug

Design of the electrical connection / FastConnect

Yes

**Mechanical data**

Material / of the enclosure

plastic

**Design, dimensions and weight**

Width

15.8 mm

Height

54 mm

Depth

39.5 mm

Net weight

29 g

**Permitted ambient conditions**

Ambient temperature

- during operating
- during storage
- during transport

0 °C

-40 ... +70 °C

-40 ... +70 °C

Relative humidity / at 25 °C / without condensation / during operating / maximum	95 %
Protection class IP	IP20
<b>Product properties, functions, components / general</b>	
Product feature / [not supplied - silicon-free]	Yes
Product component	
• PG connection socket	No
• strain relief	Yes
<b>Standards, specifications, approvals</b>	
Verification of suitability	
• RoHS conformity	Yes
• UL-registration	Yes
<b>letzte Änderung:</b>	Feb 4, 2013