



SIMATIC S7-300, Analog input SM 331, single channel Isolated 250 V AC, 6 AI thermocouples Type B, E, J, K, L, N, R, S, T Voltage: +/-25mV to +/-1V 16 bit, 50ms, 1x 40-pole

Figure similar

General information	
Product function	
Protection function	
Engineering with	
Integrated drive control	
Operating mode	
Operator control and monitoring	
Process images	
User administration	
Alarms	
Recipes/user archives	
Display	
Line display	
Resolution (pixels)	
Control elements	
Input device	
Keyboard fonts	
Touch operation	
Connection type	
Special operator controls	
Frame size/design	
Ergonomics	
Supply voltage	
Line frequency	
Mains filter	
Mains buffering	
Load voltage L+	
<ul style="list-style-type: none"> Rated value (DC) Reverse polarity protection 	24 V Yes
Load voltage 1L+	
Load voltage 2L+	
Load voltage L1	
Auxiliary voltage 1L+, load voltage 2L+	
Input voltage	
Input voltage acc. to VDE	
Input voltage acc. to UL	

Line frequency	
Input current	
from load voltage L+ (without load), max.	150 mA
from backplane bus 5 V DC, max.	100 mA
Output current	
horizontal installation	
vertical installation	
Encoder supply	
Output current	
5 V encoder supply	
24 V encoder supply	
Additional 24 V encoder supply	
Power loss	
Power loss, typ.	2.2 W
Memory	
Work memory	
Working memory for additional functions	
Battery	
Design	
CPU-blocks	
DB	
FB	
FC	
Counters, timers and their retentivity	
S7 counter	
IEC counter	
S7 times	
Data areas and their retentivity	
Flag	
Address area	
I/O address area	
of which distributed	
per integrated IO subsystem	
Process image	
Subprocess images	
Digital channels	
Analog channels	
Addressing volume	
Hardware configuration	
Formation of potential groups	
Module exchange	
Interface modules	
Number of DP masters	
Number of IO Controllers	
Number of operable FMs and CPs (recommended)	
Expansion modules	
Rack	
Submodules	
Selection of BaseUnit for connection variants	
PtP CM	
Time of day	
Clock	
Operating hours counter	
Time switching clocks	
Digital inputs	
Number of simultaneously controllable inputs	

all mounting positions	
horizontal installation	
Digital input functions, parameterizable	
Input voltage	
Input current	
for 10 k switched contact	
Internal preparation time	
Input delay (for rated value of input voltage)	
for standard inputs	
for interrupt inputs	
Encoder connection	
Connection method	
Digital outputs	
Digital output functions, parameterizable	
Control supply voltage	
Switching capacity of the outputs	
Load resistance range	
Trend key points E	
Output voltage	
Output current	
Output delay with resistive load	
Parallel switching of two outputs	
Switching frequency	
Total current of the outputs	
horizontal installation	
Total current of the outputs (per group)	
all mounting positions	
horizontal installation	
vertical installation	
Total current of the outputs (per module)	
all mounting positions	
horizontal installation	
Pulse output (passive)	
Frequency output	
Relay outputs	
Integrated high-speed cams	
Analog inputs	
Number of analog inputs	6
permissible input voltage for voltage input (destruction limit), max.	35 V; 35 V continuous, 75 V for max. 1 s (mark to space ratio 1:20)
Constant measurement current for resistance-type transmitter, typ.	0.7 mA
Input ranges	
• Voltage	Yes
• Current	No
• Thermocouple	Yes
• Resistance thermometer	No
• Resistance	No
Measuring range	
Input ranges (rated values), voltages	
• 0 to +10 V	No
• 1 V to 5 V	No
• 1 V to 10 V	No
• -1 V to +1 V	Yes
— Input resistance (-1 V to +1 V)	10 MΩ
• -10 V to +10 V	No
• -2.5 V to +2.5 V	No
• -250 mV to +250 mV	Yes
— Input resistance (-250 mV to +250 mV)	10 MΩ

• -5 V to +5 V	No
• -50 mV to +50 mV	Yes
— Input resistance (-50 mV to +50 mV)	10 MΩ
• -500 mV to +500 mV	Yes
— Input resistance (-500 mV to +500 mV)	10 MΩ
• -80 mV to +80 mV	Yes
— Input resistance (-80 mV to +80 mV)	10 MΩ
Input ranges (rated values), currents	
• 0 to 20 mA	No
• -10 mA to +10 mA	No
• -20 mA to +20 mA	No
• -3.2 mA to +3.2 mA	No
• 4 mA to 20 mA	No
Input ranges (rated values), thermocouples	
• Type B	Yes
— Input resistance (Type B)	10 MΩ
• Type C	Yes
— Input resistance (Type C)	10 MΩ
• Type E	Yes
— Input resistance (Type E)	10 MΩ
• Type J	Yes
— Input resistance (type J)	10 MΩ
• Type K	Yes
— Input resistance (Type K)	10 MΩ
• Type L	Yes
— Input resistance (Type L)	10 MΩ
• Type N	Yes
— Input resistance (Type N)	10 MΩ
• Type R	Yes
— Input resistance (Type R)	10 MΩ
• Type S	Yes
— Input resistance (Type S)	10 MΩ
• Type T	Yes
— Input resistance (Type T)	10 MΩ
• Type U	Yes
— Input resistance (Type U)	10 MΩ
• Type TXK/TXK(L) to GOST	Yes
— Input resistance (Type TXK/TXK(L) to GOST)	10 MΩ
Input ranges (rated values), resistance thermometer	
• Cu 10	No
• Ni 100	No
• Ni 1000	No
• LG-Ni 1000	No
• Ni 120	No
• Ni 200	No
• Ni 500	No
• Pt 100	No
• Pt 1000	No
• Pt 200	No
• Pt 500	No
Input ranges (rated values), resistors	
• 0 to 150 ohms	No
• 0 to 300 ohms	No
• 0 to 600 ohms	No
• 0 to 6000 ohms	No
Input ranges (rated values), strain gauges (full bridges)	
Thermocouple (TC)	
Temperature compensation	

— parameterizable	Yes
— internal temperature compensation	Yes
— external temperature compensation with Pt100	Yes
— external temperature compensation with compensations socket	Yes
— for definable comparison point temperature	Yes
Characteristic linearization	
• parameterizable	Yes
— for thermocouples	Type B, E, J, K, L, N, R, S, T, U, C, TXK, XK(L)
— for resistance thermometer	No
Connection method	
Cable length	
• shielded, max.	200 m
Analog outputs	
Output ranges, voltage	
Output ranges, current	
Connection of actuators	
Load impedance (in rated range of output)	
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit; Two's complement
• Integration time, parameterizable	Yes
• Basic conversion time (ms)	30 / 50 / 60 / 300 ms
• Integration time (ms)	10/ 16.67/ 20/ 100 ms
Analog value generation for the outputs	
Integration and conversion time/resolution per channel	
Encoder	
Connection of signal encoders	
• for voltage measurement	Yes
Connectable encoders	
Incremental encoder	
Encoder signals, incremental encoder (symmetrical)	
Encoder signals, incremental encoder (asymmetrical)	
Encoder signals, absolute encoder (SSI)	
Encoder signals, IEPE	
Drive axis	
EC motor	
Errors/accuracies	
Operational error limit in overall temperature range	
• Voltage, relative to input range, (+/-)	Operating error at 0 ... 60 °C: ±0.12% @ ±25 mV, ±0.08% @ ±50 mV, ±0.6% @ ±80 mV, ±0.05% @ ±250 mV, ±0.05% @ 500 mV, ±0.05% @ ±1 V
• Thermocouple, relative to input range, (+/-)	See manual for details
Basic error limit (operational limit at 25 °C)	
• Voltage, relative to input range, (+/-)	See manual for details
• Thermocouple, relative to input range, (+/-)	See manual for details
Power electronics	
Control of heating elements	
Load connection type	
Setpoint input	
Heating power	
Interfaces	
Video interfaces	
Touch interfaces	
MPI	
PROFIBUS DP	
PROFIBUS PA	
Supports protocol for PROFINET IO	

PROFINET functions
Industrial Ethernet
Point-to-point connection
Integrated protocol driver
Telegram length, max.
Transmission rate, 20 mA (TTY)
Transmission rate, RS 422/485
Transmission speed, RS 232
Signals
ET-Connection
EtherNet/IP
AS-Interface
WLAN
1. Interface
Interface types
Protocols
MPI
PROFIBUS DP master
Services
PROFIBUS DP slave
PROFINET IO Controller
Services
Update time for IRT
PROFINET IO Device
Services
PROFINET CBA
Open IE communication
CAN
BACnet
2. Interface
Interface types
Protocols
PROFIBUS DP master
Services
PROFIBUS DP slave
PROFINET IO Controller
Services
Update time for IRT
PROFINET IO Device
Services
PROFINET CBA
3. Interface
Interface types
Protocols
PROFIBUS DP master
Services
PROFIBUS DP slave
PROFINET IO Controller
PROFINET IO Device
Services
PROFINET CBA
4. Interface
Interface types
Protocols
PROFIBUS DP master
PROFINET IO Controller
Interface types
RJ 45 (Ethernet)

RS 232	
RS 485	
RS 422	
USB port	
Protocols	
Protocols (USB)	
Protocols (Ethernet)	
WEB characteristics	
Protocols (terminal link)	
Number of connections	
PROFINET IO Device	
Redundancy mode	
SIMATIC communication	
EtherNet/IP	
Services	
Updating times	
Redundancy mode	
Open IE communication	
Web server	
PROFIBUS DP	
PROFdrive	
DALI	
Integrated protocols	
Freeport	
3964 (R)	
OPC UA	
Communication functions	
Global data communication	
S7 basic communication	
S7 communication	
LOGO! communication	
S5 compatible communication	
Standard communication (FMS)	
PROFINET CBA (at set setpoint communication load)	
Remote interconnections with acyclic transmission	
Remote interconnections with cyclic transmission	
iPAR server	
Number of connections	
Test commissioning functions	
Status/control	
Forcing	
Diagnostic buffer	
Interrupts/diagnostics/status information	
Diagnostics function	Yes; Parameterizable
Alarms	
• Diagnostic alarm	Yes; channel by channel
• Limit value alarm	Yes; Parameterizable
• Hardware interrupt	Yes; Parameterizable
Diagnoses	
• Diagnostic information readable	Yes
Diagnostics indication LED	
• Group error SF (red)	Yes
Integrated Functions	
Monitoring functions	
Safety monitoring functions	
Counting functions	
Load cell	
Position detection	

Control technology
Step-by-step controllers
Pulse generator
Measuring functions
Operating mode for measured value acquisition
Measuring range
Accuracy
Measuring inputs for voltage
Measuring inputs for current
Measuring inputs for current (Rog. or I/U converter)
Error limits
Counter
Counting mode
External gate counters
Counter input 5 V
Counter input 24 V
Drive interface
Signal Input
Potential separation
Potential separation digital inputs
Potential separation digital outputs
Potential separation analog inputs
<ul style="list-style-type: none"> • between the channels • between the channels, in groups of • between the channels and backplane bus • between the channels and the power supply of the electronics
Yes
1
Yes
Yes
Potential separation analog outputs
Potential separation channels
Potential separation valve outputs
Potential separation counter
Potential separation controller
Isolation
Isolation tested with
2 500 V DC
EMC
Interference immunity against discharge of static electricity
Interference immunity against high-frequency electromagnetic fields
Interference immunity to cable-borne interference
Interference immunity against voltage surge
Interference immunity against conducted variable disturbance induced by high-frequency fields
Interference immunity to magnetic fields
Emission of radio interference acc. to EN 55 011
Emission of radio interference acc. to EN 55 022
Standards, approvals, certificates
Highest safety class achievable in safety mode
Highest safety class achievable for safety-related tripping of standard modules
Highest safety class achievable for deactivated dark test
Use in hazardous areas
Marine approval
Ambient conditions
Free fall
Ambient temperature during operation
Operation (vertical installation)
Air pressure acc. to IEC 60068-2-13
Vibrations
Shock testing
Resistance
Coolants and lubricants

Fire resistance
Pollutant concentrations
Hardware requirement
Processor
Graphic
Operating systems
pre-installed operating system
Runs under operating system
Software
Preinstalled
Software functions
Multi-user system
Runtime software
Runtime
Block
Adjustable parameters
Configuration
Configuration
Configuration software
Script languages (Runtime)
Programming
Programming language
Configuration examples
Software libraries
Know-how protection
Access protection
Languages
Online languages
Functionality under WinCC (TIA Portal)
Multiproject
Message system
Recipe management
Variables
Images
Image objects
Complex image objects
Attributes for dynamic objects
Lists
Archiving
Filters
Security
Data carrier support
Logging through printer
Character sets
Transfer (upload/download)
Process coupling
Functions
Functionality under WinCC Unified
Parameter set management (recipes)
Image objects
Connection method
required front connector
40-pin
ET-Connection
Terminals
Connection I/O signals
Conductor cross-section in mm ²
Conductor cross-section acc. to AWG

Dimensions	
Width	40 mm
Height	125 mm
Depth	120 mm
Weights	
Weight, approx.	272 g
Other	
Data for selecting a voltage transformer	

last modified:

3/2/2021 